



AP-5131 Access Point

Combination wired/wireless networking
for branch offices and small businesses



FEATURES

WAN and LAN Ethernet ports

Single device solution for both wired and wireless networking

Dual-radio, dual-band design; 802.11a/b/g in 2.4/5 GHz bands

Works with any standards-based IEEE WLAN

Integrated router, firewall and DHCP server

Easy to scale, upgrade and maintain

AAA server and hotspot gateway

Integrated services for authentication and public access management

Mesh networking

Allows wireless extension of existing wired or wireless networks in remote or outdoor locations

Triple methodology rogue AP detection: on-channel, mobile unit, dedicated radio dual-band scanning

Network protection through instant identification and reporting of unauthorized users

Cost-effective, secure, high-performance wired and wireless connectivity

Designed for small offices and retail locations, the AP-5131 delivers wired and wireless networking with enterprise-class performance and security in a single device. This easy-to-deploy solution offers the flexibility to connect securely to remote corporate private networks, the Internet and local network resources with the speed and reliability to support the most demanding applications, including real-time video and voice. The all-in-one AP-5131 delivers a new level of cost-efficiency and networking simplicity for employees in branch offices or telecommuters working at home. The 5131 boasts an integrated router, firewall, VPN, DHCP, AAA, hotspot gateway, and other services in one remotely manageable device, simplifying network set-up and management.

Enterprise-class security and manageability

Support for today's standards-based security protocols ensures enterprise-level protection for users on wireless laptops and other mobile devices, as well as wired computers. A wide variety of administration features provide powerful and secure control by either local, non-technical staff or remote IT professionals in the Network Operations Center.

Dual-radio 802.11a/b/g architecture

The dual-radio architecture offers the flexibility to best meet wireless LAN networking and security needs through either dual-band data services, or

single-band data services and full-band rogue AP detection, which identifies and reports unauthorized entities on the network. A complete suite of dual and single-band antennas provides the versatility to customize radio coverage for even the most challenging environments, with a minimal number of access points.

Mesh networking

To enable the extension of wireless network coverage to areas where ethernet or fiber cabling is cost-prohibitive or otherwise impractical, the AP-5131 can operate wirelessly, connecting to other access points for data backhaul, in a mesh topology. Enabling an array of applications, from simple point-to-point bridges connecting two wired networks, to complex multi-node, multi-link networks, this feature offers a cost-effective way to extend the network outdoors or in remote areas, relying on a highly resilient, self-configuring system. Taking advantage of the dual-radio architecture and the easy-to-use configuration interface, it becomes a simple task to deploy a wireless network of access points connected securely via 802.11a, providing enterprise-class 802.11b/g service.

For more information on the AP-5131, contact Motorola at +1.800.722.6234 or +1.631.738.2400, or visit us on the web at www.symbol.com/AP5131

SPECIFICATION SHEET

AP-5131
 Combination wired/wireless networking for branch offices and small businesses

802.11i, WPA2 and WPA; triple-DES IPsec encryption; VPN client

End-to-end enterprise class wired and wireless security

Wi-Fi Multimedia (WMM™) Quality of Service (QoS) and Voice prioritization

Superior performance for demanding mission critical applications, including voice and video

Java™ web-based graphical user interface; Motorola Mobility Services Platform (MSP); SNMPv3; command line interface (CLI)

Flexible management options; easy-to-use "anytime, anywhere" management

AP-5131 Specifications

Physical Characteristics	
Dimensions:	5.32 in. L x 9.45 in. W x 1.77 in. H 135 mm L x 240 mm W x 45 mm H
Weight:	1.95 lbs/0.884kg
Housing:	Metal, plenum-rated housing (UL2043)
Available Mounting Configurations:	No additional hardware required to mount on desktop, above drop ceiling, under ceiling or on wall
LEDs:	4 top mounted LEDs, 2 bottom mounted LEDs, with multiple modes indicating 802.11a/802.11g activity, power, adoption and errors
Uplink:	2 ports (WAN, LAN) Auto-sensing 10/100Base-T Ethernet
User Environment	
Operating Temperature:	-4°F – 122°F/-20°C to 50°C
Storage Temperature:	-40°F to 158°F/-40°C to 70°C
Operating Humidity:	5 to 95% RH non-condensing
Operating Altitude:	8000 ft./2438m @ 82°F/28°C
Storage Altitude:	15000 ft./4572m @ 53°F/12°C
Electrostatic Discharge:	15kV air, 8kV contact
Power Specifications	
Operating Voltage:	48V DC
Operating Current:	200mA
Integrated PoE Support:	802.3af on LAN Port
Radio Specifications	
Wireless Medium:	Direct Sequence Spread Spectrum (DSSS) and Orthogonal Frequency Division Multiplexing (OFDM)
Network Standards:	802.11a, 802.11b, 802.11g, 802.3
Data Rates Supported:	1, 2, 5.5, 6.9, 11, 12, 18, 24, 36, 48, 54 Mbps
Operating Channels:	Chan 1-35 (4920 – 5825 MHz) Chan 1-13 (2412-2472 MHz) Chan 14 (2484 MHz) Japan only Actual operating frequencies depend on regulatory rules and certification agency
Available Transmit Power Settings:	4-20 dBm

Operating Bands:	FCC	EU
	2.412 to 2.462 GHz 5.150 to 5.250 (UNII -1) 5.250 to 5.350 (UNII -2) 5.725 to 5.825 (UNII -3) 5.725 to 5.850 (ISM)	2.412 to 2.472 GHz 5.150 to 5.250 GHz 5.150 to 5.350 GHz 5.470 to 5.725 GHz (Country Specific)
	Japan 2.412 to 2.484GHz 4.900 to 5.000 GHz 5.150 to 5.250 GHz	
Receiver Sensitivity:	Radio .11a (dBm) 10% PER for 1000 bytes IEEE 802.11a sect 17.3.10.1 (MIN) & 17.3.10.4 (MAX)	6 Mbps -91 9 Mbps -89 12 Mbps -87 18 Mbps -83 24 Mbps -81 36 Mbps -78 48 Mbps -74 54 Mbps -73
	Radio .11g (dBm) 10% PER for 1000 Octets IEEE 802.11g sect 19.5.1 (MIN) & 19.5.3 (MAX)	6 Mbps -89 9 Mbps -88 12 Mbps -85 18 Mbps -82 24 Mbps -80 36 Mbps -77 48 Mbps -72 54 Mbps -70
	Radio .11b (dBm) 8% PER for 1,024 Octets	1 Mbps -94 2 Mbps -90 5.5 Mbps -88 11 Mbps -84

Regulatory				
Standards Compliance:	Wi-Fi: 802.11a/b/g, WPA2, WMM			
Product Safety Certs.:	UL / cUL 60950-1, IEC / EN60950-1, UL2043, TUV GS, RoHS			
Radio Approvals:	FCC (USA), Industry Canada, CE (Europe), TELEC (Japan)			
Part Numbers	Single Radio 802.11a/g	Dual Radio 802.11a+g	Dual Band antenna	PoE supply
AP-5131-40020-WW	•			
AP-5131-40021-WWR	•			•
AP-5131-40022-WW	•		• (x2)	
AP-5131-40023-WWR	•		• (x2)	•
AP-5131-13040-WW		•		
AP-5131-13041-WWR		•		•
AP-5131-13042-WW		•	• (x4)	
AP-5131-13043-WWR		•	• (x4)	•



motorola.com

Part number SS-AP5131. Printed in USA 03/07. MOTOROLA and the Stylized M Logo and SYMBOL and the Stylized SYMBOL Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. ©2007 Motorola, Inc. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.